



## 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	EXTENSION RING	PORT		OPTICAL PERFORMANCE	
<b>WIDE ANGLE</b> <small>APSC</small>	<b>N120 CINEMA SYSTEM</b> <small>( RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC )</small>	Canon EF-S 10-18mm f/4.5-5.6 IS STM	<b>16340</b> RC1018 Gear Set		<b>85204</b> WACP - 2	On APS-C Sensor	Lens FOV Converted FOV	108-75° 128-85°
		Canon EF-S 10-22mm f/3.5-4.5 IS USM	<b>16303 + 16304</b> RC1022-Z + RC1022-F	<b>21110</b> Extension Ring 10 with Screws	<b>85204</b> WACP - 2	On APS-C Sensor	Lens FOV Converted FOV	108-63° 128-72°
		Tokina AT-X 11-20mm F2.8 PRO DX	<b>16328</b> RTC1120 Gear Set	<b>21120</b> Extension Ring 20 with Lock	<b>85204</b> WACP - 2	On APS-C Sensor	Lens FOV Converted FOV	100-68° 118-78°
		Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	<b>16309 + 16310</b> RSC1116-Z + RSC1116-F	<b>21110</b> Extension Ring 10 with Screws	<b>85204</b> WACP - 2	On APS-C Sensor	Lens FOV Converted FOV	110-81° 118-92°
<b>WIDE ANGLE</b> <small>FULL FRAME</small>	<b>N120 CINEMA SYSTEM</b> <small>( RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC )</small>	Canon EF 16-35mm f/2.8 II USM	<b>19527 + 19542</b> C1635II-Z +  C1635II-F	<b>21130</b> Extension Ring 30 with Lock	<b>85204</b> WACP - 2	On APS-C Sensor  On Full Frame Sensor	Lens FOV Converted FOV  Lens FOV Converted FOV	84-44° 98-51°  107-63° 128-72°
		Canon EF 16-35mm f/2.8 III USM	<b>16325</b> RC1635III Gear Set	<b>21150</b> Extension Ring 50 with Lock	<b>85204</b> WACP - 2	On APS-C Sensor  On Full Frame Sensor	Lens FOV Converted FOV  Lens FOV Converted FOV	84-44° 98-51°  107-63° 128-72°
		Canon EF 16-35mm f/4L IS USM	<b>16317 + 16318</b> RC1635f4-Z + RC1635f4-F	<b>21130</b> Extension Ring 30 with Lock	<b>85204</b> WACP - 2	On APS-C Sensor  On Full Frame Sensor	Lens FOV Converted FOV  Lens FOV Converted FOV	84-44° 98-51°  107-63° 128-72°
		Canon RF 14-35mm f/4L IS USM	<b>16342</b> CR1435 Gear Set	<b>21110</b> Extension Ring 10 with Screws	<b>85204</b> WACP - 2	On APS-C Sensor  On Full Frame Sensor	Lens FOV Converted FOV  Lens FOV Converted FOV	89-42° 104-48°  114-63° 140-72°
		Canon RF 15-35mm f/2.8L IS USM	<b>16341</b> CR1535 Gear Set	<b>21135</b> Extension Ring 35 with Lock	* <b>85204</b> WACP - 2	On APS-C Sensor  On Full Frame Sensor	Lens FOV Converted FOV  Lens FOV Converted FOV	84-42° 98-48°  110-63° 133-72°
<b>WIDE ANGLE</b> <small>FX</small>	<b>N120 NIKON F-MOUNT</b>	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	<b>19138</b> N1635-Z  <b>19138 + 19142</b> N1635-Z + N1635-F	<b>21150</b> Extension Ring 50 with Lock  <b>21240</b> Extension Ring 40 with Focus Knob	* <b>85204</b> WACP - 2  <b>85204</b> WACP - 2	Lens FOV Converted FOV  Lens FOV Converted FOV	105-63° 128-72°  105-63° 128-72°	
		Nikon AF-S 17-35mm f/2.8D IF-ED	<b>19130</b> N1735-Z	<b>21130</b> Extension Ring 30 with Lock	<b>85204</b> WACP - 2	Lens FOV Converted FOV	104-63° 123-72°	

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
\* Recommended port system based on best optical performance



## 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE		
N120 NIKON Z-MOUNT	STANDARD ZOOM FULL FRAME	Nikkor Z 24-70mm f/2.8 S Lens	19157 NZ2470f2.8S-Z	21125 Extension Ring 25 with Lock	85204 WACP - 2	Lens FOV	84-46°	
	WIDE ANGLE FULL FRAME	Nikkor Z 14-24mm f/2.8 S	19160 NZ1424-Z	21110 Extension Ring 10 with Screws	85204 WACP - 2	Lens FOV	114-87°	
		Nikkor Z 14-30mm f/4 S	19156 NZ1430-Z		85204 WACP - 2	Converted FOV	98-56°	
N120 CANON EF-MOUNT	WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19549 C1018-Z		85204 WACP - 2	Lens FOV	108-75°	
		Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z	21110 Extension Ring 10 with Screws	85204 WACP - 2	Converted FOV	128-85°	
		Tokina AT-X 11-20mm F2.8 PRO DX	19573 CT1120-Z	21120 Extension Ring 20 with Lock	85204 WACP - 2	Lens FOV	108-63°	
		Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19530 TC1116-Z	21110 Extension Ring 10 with Screws	85204 WACP - 2	Converted FOV	128-72°	
	WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z	21130 Extension Ring 30 with Lock	85204 WACP - 2	Lens FOV	107-63°	
			19527 + 19542 C1635II-Z + C1635II-F	21230 Extension Ring 30 with Focus Knob	* 85204 WACP - 2	Converted FOV	128-72°	
		Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z	21150 Extension Ring 50 with Lock	85204 WACP - 2	Lens FOV	107-63°	
			19554 + 19555 C1635III-Z + C1635III-F	21250 Extension Ring 50 with Focus Knob	* 85204 WACP - 2	Converted FOV	128-72°	
	Canon EF 16-35mm f/4 IS USM	19548 C1635f4-Z	21130 Extension Ring 30 with Lock	85204 WACP - 2	Lens FOV	108-63°		
		19548 + 19572 C1635f4-Z + WC1635f4-F	21235 Extension Ring 35 with Focus Knob	85204 WACP - 2	Converted FOV	128-72°		
	N120 CANON RF-MOUNT	WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21110 Extension Ring 10 with Screws	85204 WACP - 2	Lens FOV	114-63°
			Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z	21135 Extension Ring 35 with Lock	85204 WACP - 2	Converted FOV	140-72°
19569 + 19571 CR1535-Z + WCR1535-F				21235 Extension Ring 35 with Focus Knob	* 85204 WACP - 2	Lens FOV	110-63°	
						Converted FOV	133-72°	

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

\* Recommended port system based on best optical performance



## 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
N120 PANASONIC L-MOUNT	WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	<b>19728</b> PL1635-Z			<b>85204</b> WACP - 2		Lens FOV 105-63° Converted FOV 128-72°
	SIGMA EF-MOUNT (FF, with Sigma Mount Converter MC-21)	Sigma 14-24mm F2.8 DG HSM   Art	<b>19564 + 19726</b> SC1424A-Z + SLE1424-F		<b>21125</b> Extension Ring 25 with Lock	<b>85204</b> WACP - 2		Lens FOV 94-84° Converted FOV 115-98°
		Sigma 14-24mm F2.8 DG DN Art	<b>19564</b> SLE1424-Z		<b>21125</b> Extension Ring 25 with Lock	<b>85204</b> WACP - 2		Lens FOV 94-84° Converted FOV 115-98°
N120 FUJIFILM G-MOUNT	MACRO MEDIUM FORMAT	Laowa 17mm f/4 GFX Zero-D	<b>19824 + 19825</b> GL17-A + GL17-F		<b>21235</b> Extension Ring 35 with Focus Knob	<b>85204</b> WACP - 2		Lens FOV 114° Converted FOV 140°
	WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 23mm F4 R LM WR			<b>21120</b> Extension Ring 20 with Lock	<b>85204</b> WACP - 2		Lens FOV 100° Converted FOV 118°
N100 SONY E-MOUNT	STANDARD ZOOM FULL FRAME	Sony SEL2470GM FE 24-70mm F2.8 GM	<b>37151</b> SFE2470GM-Z	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>21130</b> Extension Ring 30 with Lock	<b>85204</b> WACP - 2		Lens FOV 84-34° Converted FOV 98-72° Zoom Range 24-35mm
			<b>37151 + 37152</b> SFE2470GM-Z + SFE2470GM-F					
		Sony SEL2470Z Vario-Tessar T* FE 24-70mm F4 ZA OSS	<b>37149</b> SE2470-Z	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>85204</b> WACP - 2		Lens FOV 84-34° Converted FOV 98-72° Zoom Range 24-35mm
		<b>37149 + 37148</b> SE2470-Z +						
		Sigma 24-70mm f/2.8 DG DN Art	<b>37171</b> SSF2470-Z	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>21120</b> Extension Ring 20 with Lock	<b>85204</b> WACP - 2		Lens FOV 84-64° Converted FOV 98-74° Zoom Range 24-34mm
WIDE ANGLE FULL FRAME		Sony FE 14mm f/1.8 GM		<b>37306</b> N100 to N120 25mm Port Adaptor		<b>85204</b> WACP - 2		Lens FOV 114° Converted FOV 140°

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

\* Recommended port system based on best optical performance



## 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 FOR FULL FRAME 14MM EQUIVAMENT LENS TO 140° FULL ZOOM-THROUGH

		CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
N100 SONY E-MOUNT	WIDE ANGLE FULL FRAME	Sony SEL1635GM FE 16-35mm F2.8 GM	<b>37155</b> SFE1635GM-Z  <b>37155 + 37156</b> SFE1635GM-Z + SFE1635GM-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>21130</b> Extension Ring 30 with Lock	<b>85204</b> WACP - 2	Lens FOV Converted FOV	107-63° 128-77°
		Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	<b>37145 + 37146</b> SE1635-Z + SE1635-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>21110</b> Extension Ring 10 with Screws	<b>85204</b> WACP - 2	Lens FOV Converted FOV	107-63° 128-77°
		Sony FE 24mm f/1.4 GM		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>85204</b> WACP - 2	Lens FOV Converted FOV	84° 98°
		Sigma 14-24mm F2.8 DG DN	<b>19726</b> SLE1424-Z	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>21125</b> Extension Ring 25 with Lock	<b>85204</b> WACP - 2	Lens FOV Converted FOV Zoom Range	94-84° 115-98° 20-24mm
		Tamron 17-28mm f/2.8 Di III RXD	<b>37157</b> STE1728-Z  <b>37157 + 37158</b> STE1728-Z + STE1728-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>85204</b> WACP - 2	Lens FOV Converted FOV	104-75° 123-89°

### 85204 0.57X WIDE ANGLE CONVERSION PORT WACP-2

#### Package includes :

Hard Lens Cap  
Rear Port Cap  
Spare O-ring 90140  
Lubricant  
Cleaning Cloth  
Carrying Bag

#### Specification

Dimension ( dia x length ) 267 x 220 mm  
Weight in Air 7.35 kg  
Buoyancy in Water 0.27 kg  
Body Construction Hard-anodized aluminum alloy  
Lens Construction 4 Elements in 4 Groups  
Lens Coating Anti-reflection Coating on both sides  
Lens Mount N120 Port Mount  
Depth Rating 100m

Focal Distance From front element of lens to infinity  
Field of View (Underwater) 140° (ref 14mm equiv.)

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

\* Recommended port system based on best optical performance