



N120 PORT SYSTEM FOR FUJIFILM G-MOUNT CAMERA SYSTEM

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO MEDIUM FORMAT	Fujifilm GF 120mm f/4 Macro R LM OIS WR	19823 GF120-F	21160 Extension Ring 60 with Lock	18701 Macro Port 60	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.0X Working Distance 65-93mm
	Fujifilm GF 120mm f/4 Macro R LM OIS WR with HOYA +2 Close Up Diopter	19823 GF120-F	21170 Extension Ring 70 with Lock	18701 Macro Port 60	83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 25.7° Converted FOV 60°/100°/130°
	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17-A + GL17-F	21235 Extension Ring 35 with Focus Knob 21135 + 21140 Extension Ring 35 with Lock + 40 21135 + 21150 Extension Ring 35 with Lock + 50	* 85204 WACP - 2 * 18815 250mm Optical Glass Wide Angle Port II 18812 230mm Optical Glass Wide Angle Port II			Lens FOV 114° Converted FOV 140°
STANDARD ZOOM MEDIUM FORMAT	Fujifilm GF 32-64mm f/4 R LM WR	19822 GF3264-Z	21140 + 21160 Extension Ring 40 with Lock + 60	18815 250mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.50m</i> 18805 10" acrylic wide angle port <i>* depth rating 150m</i> <i>* Minimum focus distance from port to subject is 0.45m at 32mm, 1.17m at 64m</i>			
	Fujifilm GF 63mm f/2.8 R WR			18701 Macro Port 60			
WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 23mm F4 R LM WR		21120 Extension Ring 20 with Lock 21160 Extension Ring 60 with Lock	* 85204 WACP - 2 18812 230mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.38m</i> * 18815 250mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.24m</i>			Lens FOV 100° Converted FOV 118°
	Fujifilm GF 45mm f/2.8 R WR		21130 Extension Ring 30 with Lock	18701 Macro Port 60 * 85201 WACP - 1			Lens FOV 63° Converted FOV 109°

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance