



DL (Dry Lock) Port System Charts for Nikon Z-Mount Mirrorless Cameras

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

LENSES REFERENCING “+4 DIOPTER REQUIRED”

[Why Your Lens May Need a +4 Diopter Underwater](#)

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (ø 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

HELPFUL LINKS

[When to Use a Compact 8" Dome Port Underwater](#)

[How to Polish an Acrylic Dome Port](#)

[Dealing with Droplets when Shooting Split Shots](#)

[Why You Need a Fisheye Lens Underwater](#)

[The Right Lens for Every Situation Underwater](#)

[5 Situations Where You Need a Strobe Underwater](#)

Nikon Z-mount Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8-15 mm Nikon f/3.5-4.5E ED Fisheye + Nikon Mount Adapter FTZ See Installation See Review	Larger dome is best for split shots (half-in, half-out of the water). Superior edge sharpness compared to shorter port option. Dome shade must be removed to eliminate vignetting (dark shadows around the edges of the image). Zoom gear may alternatively be used to manually focus. Product(s) required: 75340 Dome Port 75020 Extension 5509.28 Zoom (Focus) Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. Lens shade must be removed. Dome shade must be removed to eliminate vignetting (dark shadows around the edges of the image). Zoom gear may alternatively be used to manually focus. Product(s) required: 75344 Dome Port 75028 Extension 5509.28 Zoom (Focus) Gear	Larger dome is best for split shots (half-in, half-out of the water). Dome shade must be removed to eliminate vignetting (dark shadows around the edges of the image). A longer port is recommended for better edge sharpness. Zoom gear may alternatively be used to manually focus. Product(s) required: 75340 Dome Port 5509.28 Zoom (Focus) Gear
10.5 mm Nikon AF DX f/2.8 G ED Fisheye + Nikon Mount Adapter FTZ	Some vignetting (dark shadows in the corners of the image) will be present. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight		
12-28 mm Nikon Z DX f/3.5-5.6 PZ VR See Installation	Larger dome is best for split shots (half-in, half-out of the water). Zoom gear may alternatively be used to manually focus. Product(s) required: 75340 Dome Port 5509.28 Zoom (Focus) Gear 0923.35 Anti-Reflection Ring 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. Zoom gear may alternatively be used to manually focus. Product(s) required: 75344 Dome Port 5509.28 Zoom (Focus) Gear 0923.35 Anti-Reflection Ring	A flat port has a magnifying effect underwater. Slight vignetting (dark shadows around the edges of the image) will be present. Zoom gear may alternatively be used to manually focus. Product(s) required: 75303 Flat Port 5509.28 Zoom (Focus) Gear 0923.35 Anti-Reflection Ring

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
14-24 mm Nikon Z f/2.8 S	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.43 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75050 Extension 5509.43 Zoom Gear	
14-24 mm Nikon f/2.8G ED + Nikon Mount Adapter FTZ	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75037 Extension 75042 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75037 Extension 75042 Extension 5509.28 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75028 Extension 75050 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight
14-24 mm Sigma f/2.8 DG HSM A	Zoom not supported. Lens must be pre-set and used at a fixed focal length. AF only. Product(s) required: 75340 Dome Port 75020 Extension 75050 Extension Optional accessories: 47140 Trim Weight		
14-30 mm Nikon Z f/4 S See Installation See Review See Video Review	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75050 Extension 5509.31 Zoom Gear 0923.32 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75050 Extension 5509.31 Zoom Gear 0923.32 Anti-Reflection Ring	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
15mm Sigma f/2.8 EX DG Diagonal Fisheye + Nikon Mount Adapter FTZ	MF only. <u>Product(s) required:</u> 75340 Dome Port 5509.28 Focus Gear <u>Optional accessories:</u> 47140 Trim Weight		
16 mm Viltrox AF f/1.8 FE	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 75020 Extension <u>Optional accessories:</u> 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Dome Port 75028 Extension	
16-35 mm Nikon f/4G ED VR + Nikon Mount Adapter FTZ	Larger dome is best for split shots (half-in, half-out of the water). Trim weight set recommended. AF only. <u>Product(s) required:</u> 75340 Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. Trim weight set recommended. AF only. <u>Product(s) required:</u> 75344 Dome Port 75042 Extension 75050 Extension 5509.28 Zoom Gear	
16-50 mm Nikon Z f/3.5-6.3 DX VR	Compact and lightweight for travel. Better for close focus wide angle. AF only. <u>Product(s) required:</u> 75344 Dome Port 5509.27 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 5509.27 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
17-35 mm Nikon f/2.8D ED-IF AF-S + Nikon Mount Adapter FTZ	Larger dome is best for split shots (half-in, half-out of the water). Trim weight set recommended. AF only. Product(s) required: 75340 Dome Port 75028 Extension 75050 Extension 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. Trim weight set recommended. AF only. Product(s) required: 75344 Dome Port 75028 Extension 75050 Extension 5509.28 Zoom Gear	
17-28 mm Nikon Z f/2.8	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 5509.28 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75020 Extension 5509.28 Zoom Gear	
18-35 mm Nikon f/3.5-4.5G ED + Nikon Mount Adapter FTZ	Larger dome is best for split shots (half-in, half-out of the water). Trim weight set recommended. AF only. Product(s) required: 75340 Dome Port 75020 Extension 75042 Extension 5509.27 Zoom Gear Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. Trim weight set recommended. AF only. Product(s) required: 75344 Dome Port 75020 Extension 75042 Extension 5509.27 Zoom Gear	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
18-105 mm Nikon AF-S DX f/3.5-5.6G ED VR + Nikon Mount Adapter FTZ	Superior edge sharpness compared to shorter port option. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75028 Extension 75050 Extension 5509.71 Zoom Gear Optional accessories: 47140 Trim Weight	A longer port is recommended for better edge sharpness. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 75042 Extension 5509.71 Zoom Gear	
20 mm Nikon Z f/1.8 S	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: 75340 Dome Port 75037 Extension Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75037 Extension	
24 mm Nikon Z f/1.8 S	Superior edge sharpness compared to shorter port option. AF only. Product(s) required: 75340 Dome Port 75020 Extension Optional accessories: 47140 Trim Weight	Compact and lightweight for travel. Better for close focus wide angle. AF only. Product(s) required: 75344 Dome Port 75020 Extension	A longer port is recommended for better edge sharpness. AF only. Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight
24-50 mm Nikon Z f/4-6.3 See Installation	Compact and lightweight for travel. AF only. Product(s) required: +4 Diopter Required 75344 Dome Port 5509.28 Zoom Gear 0923.36 Anti-Reflection Ring	Larger dome is best for split shots (half-in, half-out of the water). AF only. Product(s) required: +4 Diopter Required 75340 Dome Port 5509.28 Zoom Gear 0923.36 Anti-Reflection Ring Optional accessories: 47140 Trim Weight	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
24-70 mm Nikon Z f/2.8 S	AF only. <u>Product(s) required:</u> +4 Diopter Required 75340 Dome Port 75020 Extension 75050 Extension 5509.32 Zoom Gear 0923.33 Anti-Reflection Ring <u>Optional accessories:</u> 47140 Trim Weight		
24-70 mm Nikon Z f/4 S See Installation	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 75344 Dome Port (2) 75028 Extensions 5509.28 Zoom Gear	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 75050 Extension 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight	
24-120 mm Nikon Z f/4 S	AF only. <u>Product(s) required:</u> +4 Diopter Required 75340 Dome Port 75020 Extension 75042 Extension 5509.46 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight System		
28-75 mm Nikon Z f/2.8	Larger dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 75340 Dome Port 75037 Extension 5509.28 Zoom Gear <u>Optional accessories:</u> 47140 Trim Weight		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
35 mm Nikon Z f/1.2 S	The magnifying effect of a flat port is good for close-up photography. The front of the port is 67mm threaded and accepts 3" diameter filters. AF only. Product(s) required: 75301 Flat Port 75020 Extension 75042 Extension	Provides the full angle of coverage underwater. Compact and lightweight for travel. AF only. Product(s) required: 75344 Dome Port 75037 Extension 75050 Extension	Provides the full angle of coverage underwater. AF only Product(s) required: 75340 Dome Port 75020 Extension 75042 Extension Optional accessories: 47140 Trim Weight
35 mm Nikon Z f/1.4 35 mm Nikon Z f/1.8 S	The magnifying effect of a flat port is good for close-up photography. The front of the port is 67mm threaded and accepts 3" diameter filters. AF only. Product(s) required: 75301 Flat Port	Provides the full angle of coverage underwater. Compact and lightweight for travel. AF only. Product(s) required: 75344 Dome Port 75020 Extension	Provides the full angle of coverage underwater. Larger dome is best for split shots (half-in, half-out of the water). AF only Product(s) required: 75340 Dome Port Optional accessories: 47140 Trim Weight
50 mm Nikon Z f/1.8 S	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded and accepts 3" diameter filters. AF only. <i>Corrected 2/22/24</i> Product(s) required: 75301 Flat Port	Provides the full angle of coverage underwater. Compact and lightweight for travel. +4 diopter is required for this lens to focus underwater behind a dome port. Lens will not focus at infinity above water with a diopter attached. AF only. <i>Corrected 2/22/24</i> Product(s) required: +4 Diopter Required 75344 Dome Port 75020 Extension	Provides the full angle of coverage underwater. +4 diopter is required for this lens to focus underwater behind a dome port. Lens will not focus at infinity above water with a diopter attached. AF only. Product(s) required: +4 Diopter Required 75340 Dome Port Optional accessories: 47140 Trim Weight

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
50 mm Nikon Z f/2.8 MC	The magnifying effect of a flat port is good for macro photography. External diopters not recommended due to the spacing between the lens and the front of the port. AF only. <u>Product(s) required:</u> 75301 Flat Port	The magnifying effect of a flat port is good for macro photography. AF only. <u>Product(s) required:</u> 75303 Flat Port	
60 mm Nikon AF-S f/2.8G ED + Nikon Mount Adapter FTZ	AF only. <u>Product(s) required:</u> 75301 Flat Port 75028 Extension		
70 mm Sigma f/2.8 DG Macro Art + Nikon Mount Adapter FTZ	AF only. <u>Product(s) required:</u> 75301 Flat Port (2) 75042 Extensions		
90 mm Tamron f/2.8 Di III VXD	AF only. <u>Product(s) required:</u> 75301 Flat Port 75020 Extension 75028 Extension		
105 mm Nikon Z MC f/2.8 VR S See MF Gear Installation	Recommended if using external wet diopters for super-macro. AF only. <u>Product(s) required:</u> 75301 Flat Port 75020 Extension 75028 Extension <u>Optional accessories:</u> 5509.72 Focus Gear	Approximately 1/8" gap between the front of the lens and the back of the port glass. AF only. <u>Product(s) required:</u> 75301 Flat Port 75050 Extension	No attachment of external wet lenses. AF only. <u>Product(s) required:</u> 75303 Flat Port 75028 Extension 75037 Extension
105 mm Nikon AF-S f/2.8G IF-ED VR + Nikon Mount Adapter FTZ	AF only. <u>Product(s) required:</u> 75301 Flat Port 75020 Extension 75042 Extension		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
105 mm Sigma f/2.8 EX DG OS HSM Macro + Nikon Mount Adapter FTZ	AF only. <u>Product(s) required:</u> 75301 Flat Port (2) 75037 Extensions		